

NLV-3101

Fixed position 2D Imager

HIGHLIGHTS

- High speed scanning
- Data editing program
- Most compact 2D scanner
- LED aiming
- Various interfaces



NLV-3101

Basic product specifications

OPERATING INDICATORS

VISUAL: 1 LED (red/green/orange) **NON-VISUAL:** Buzzer

OPERATING KEYS

ENTRY OPTIONS: 1 scan key

COMMUNICATION

RS232: DB9 PTF connector with external power supply **KEYBOARD WEDGE:** Mini-DIN6 connector with external power supply **USB:** Ver. 2.0, VCP, USB-A connector

POWER

VOLTAGE REQUIREMENT: 6V +/- 5% **CURRENT CONSUMPTION:** Max. 200mA

2D IMAGER OPTICS

LIGHT SOURCE: Aiming green LED, illumination LEDs **SCAN METHOD:** CMOS area sensor, 752 x 480 pixels, gray scale **SCAN RATE:** Up to 60 fps **IMAGE FORMAT:** Windows Bitmap, JPEG, TIFF **GRADULATION:** 256, 16, 2 **IMAGE OUTPUT MODE:** 4 resolutions (full, 1/2, 1/3, 1/4), 2 ranges (horizontal, vertical) **READING PITCH ANGLE:** -50 to 0°, 0 to +50° **READING SKEW ANGLE:** -50 to 0°, 0 to +50° **READING TILT ANGLE:** 360° **CURVATURE:** R>16 mm (10-digit Codabar), R>20 mm (12-digit UPC) **MIN. RESOLUTION AT PCS 0.9:** 0.169 mm / 7 mil at PDF417, 0.212 mm / 8 mil at QR Code and DataMatrix **MIN. PCS VALUE:** 0.3 **FIELD OF VIEW:** Horizontal 40.6°, Vertical 26.4° **DEPTH OF FIELD:** At Code 39, 85 - 125 mm / 3.35 - 4.92 in (0.127 / 5 mil), 65 - 205 mm / 2.56 - 8.07 in (0.254 mm / 10 mil), 60 - 295 mm / 2.36 - 11.61 in (0.508 mm / 20 mil) **DEPTH OF FIELD:** At QR Code, 90 - 115 mm / 3.54 - 4.53 in (0.212 mm / 8.4 mil), 55 - 195 mm / 2.17 - 7.68 in (0.381 mm / 15 mil)

SUPPORTED SYMBOLOGIES

BARCODE (1D): UPC-A, UPC-A Add-on, UPC-E, UPC-E Add-on, EAN-13, EAN-13 Addon, EAN-8, EAN-8 Add-on, JAN-8, JAN-13, Code 39, Tri-Optic, Codabar (NW-7), Industrial 2 of 5, Interleaved 2 of 5, S-Code, IATA, Code 93, Code 128, MSI/Plessey, UK/Plessey, TELEPEN, Matrix 2of5, Code 11, GS1 DataBar, GS1 DataBar Limited, GS1 DataBar Expanded, Composite GS1-DataBar, Composite GS1-128, Composite EAN, Composite UPC **POSTAL CODE:** Chinese Post, Korean Postal Authority code **2D CODE:** PDF417, MicroPDF417, Codablock F, QR Code, Micro QR Code, DataMatrix (ECC 200), MaxiCode (Modes 2 to 5), Aztec Code, Chinese Sensible Code, Passport MRZ (OCR-B)

DURABILITY

TEMPERATURE IN OPERATION: -20 to 50 °C / -4 to 122 °F **TEMPERATURE IN STORAGE:** -20 to 60 °C / -4 to 140 °F **HUMIDITY IN OPERATION:** 20 - 85% (noncondensing) **HUMIDITY IN STORAGE:** 20 - 90% (non-condensing) **AMBIENT LIGHT IMMUNITY:** Fluorescent 10,000 lx max, Direct sun 100,000 lx max, Incandescent 10,000 lx max **ANTISTATIC ELECTRICITY:** 15kV (non-destructive) **DROP TEST:** 0.75 m / 2.5 ft drop onto concrete surface **VIBRATION TEST:** 10 - 100 Hz with 2G for 1 hour **PROTECTION RATE:** IP 65

PHYSICAL

DIMENSIONS (W X H X D): 33 x 24 x 41.1 mm / 1.30 x 0.94 x 1.62 in **WEIGHT BODY:** Ca. 30 g / 1.06 oz (excl. cable) **CASE:** ABS, Black

REGULATORY & SAFETY

PRODUCT COMPLIANCE: CE, FCC Class B, VCCI Class B, RoHS, IEC 62471, EN55022, EN55024, FDA CDRH Class II

