

X-530

LASER

BARCODE SCANNER



HIGHLIGHTS

- Visible laser 650nm
- Support many different languages
- 150times/sec Scanning Speed
- Read All Standard 1D Barcode

X-530

Laser Barcode Scanner



Features

1. Traditional Durable Interface: USB/KB/COM Supported
2. Holder Optional
3. Ergonomic design, comfortable to use
4. Long Lifespan Button
5. Read all standard 1D Bar Code

Specifications

• Light Source	Visible laser 650nm	• Operating Temperature	-20°C-50°C
• Error Rate	1/5,000,000	• Storage Temperature	-20°C-60°C
• Safety	According to national laser safety standard Class2	• Operating Humidity	0-95%
• Barcode Type	1D barcode like UPC-A, UPC-E, EAN-13, EAN-8, ISBN/ISSN, Code 39, Codabar, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code128, Code93, Code 11, MSI/PIESSEY, UK/PLESSEY, UCC/EAN128 code, etc.	• Storage Humidity	5%-95%
• Supported Interfaces	Built-in PS/2 keyboard, RS-232 serial, standard 2.0USB interface	• Input Voltage	DC 5V±5%
• Trigger Mode	Trigger buttons, automatic successive scanning, automatic scintillation scanning	• Operating Current	50ma(operating mode); 30ma(standby mode); 100ma(maximum peak)
• Baud Rate	RS232baudrate: 2400-38400	• Quiescent Current	20mA
• Bar Width	Minimum 0.1mm(4mils)	• Shock Resistance	Pass 1.5m free fall test
• Depth of	2-9cm(0.1mm bar width);	• Electromagnetic Interference	According to en8001, par1 standard
• Scanning Field	3-40cm(0.3mm bar width)	• Dustproof/Waterproof	According to iec529, ip42 standard
• Scanning Speed	150times/sec	• Scanner Size	LxWxH: 20cm x 6.5cm x 5.8cm
• Scanning Distance	10-600mm Elevation angle 60°, Inclination angle 45°	• Shell Material	ABS+PVC+PC
		• Language	Support many different languages



Singapore(HQ)

All ID Asia Pte Ltd
+65-677-0075
enquiry@allid.com.sg
www.allid.com.sg

Malaysia

PT All ID Asia Sdn Bhd
+603-8075-1888
enquiry@allid.com.my
www.allid.com.my

Indonesia

PT All ID Indonesia
+62 21-4517-330
enquiry@allid.co.id
www.allid.co.id

Myanmar

All ID Myanmar
+951-652265
enquiry@allid.com.mm
www.allid.com.mm