

Polaroid



P200 Direct-to Card Printer

Polaroid P200 Direct-to-Card Printer is all about value and versatility.

With single or dual-sided printing, secure card encoding options, and USB + ethernet connectivity, it's the perfect budget-friendly printer for a variety of applications.



Small Footprint

Allows users to work effectively in any location or workstation size.

Affordable

The P200 card printer and its supplies are competitively priced to fit modest budgets.

Efficient

Print up to 880 single-sided monochrome cards per hour; 225 full-color single-sided cards per hour.

Versatile

- Single or dual-sided printing
- USB & ethernet connectivity
- Contact & contactless smart card encoding

Secure Card Options

Smart card and magnetic stripe encoding options allow you to create secure ID cards to give authorized users secure access to facilities, networks, and other privileges.

ID Applications

- Corporate IDs
- Student IDs
- Retail gift and loyalty cards
- Membership ID cards
- Transportation cards

Polaroid



P200 Specifications

Print technology	Dye sublimation
Print capabilities	Single or dual-sided
Print resolution	300 dots per inch
Print speed**	Single-sided full-color (YMCKT): up to 225 cards per hour (cph) Single-sided monochrome: up to 880 cph
Card capacity	Input hopper: 125 cards Output hopper: 25 cards Reject hopper: 10 cards
Card Sizes	Thickness: 0.01 in. – 0.04 in. (0.25 mm – 1.016 mm) Dimension: CR-80, CR-79
Operating Environment	60°F – 95°F (15°C – 35°C)
Physical Dimensions	L 17.4 in x W 8.9 in x H 9 in / 44.2 cm x 22.6 cm x 22.9 cm
Weight	11.3 lbs. / 5.13 kg (varies with options)
Connectivity	USB and Ethernet
Operating System	Windows 10 versions, 32- and 64-bit Windows 8.1, 32- or 64-bit Windows Server 2019 Windows Server 2016
Warranty	24 Months (**Warranty period may vary by territory. Please check with your point of purchase.)

Optional Features and Supplies*:

Magnetic stripe encoding	ISOA/IAT
Smart card encoding	Loosely coupled: • Contact: ISO7816 T=0 (T=1) (dual-sided only) • Contactless: ISO 14443 A/B, ISO 15693, MIFARE, MIFARE® DESFire® EV1/ EV2, HID Prox, iClass, iClass SE, iClass Seos, dual-sided only: Felica
Color ribbons**	YMCKT: 250/500 images ymckT: 650 images YMCKT-KT: 350 images ymckT-KT: 435 images
Monochrome ribbons***	Black: 1,500 images White: 1,500 images Additional monochrome options available

* All supply yields are estimates and vary based on use conditions.

** Color Panel Ribbons state the absolute maximum yield possible.

*** Monochrome Ribbons state the maximum yield based on full card print coverage. Our ribbon conservation technology enables monochrome ribbons to increase yield based on actual images printed for each card.

Polaroid



Authorized Licensee

Singapore (HQ)

All ID Asia Pte Ltd
+65 6778 0075
enquiry@allid.com.sg
www.allid.com.sg

Malaysia

All ID Asia Sdn Bhd
+603 8075 1888
enquiry@allid.com.my
www.allid.com.my

Indonesia

PT All ID Indonesia
+62 21 2248 4441
enquiry@allid.co.id
www.allid.co.id

Myanmar

All ID Myanmar
+959 77749 9949
enquiry@allid.com.mm
www.allid.com.mm

Philippines

All ID Philippines Inc.
+632 8775 1090
enquiry@allid.com.ph
www.allid.com.ph

Asia-Pacific Sales Representations: Bangladesh, Brunei, Cambodia, China, Hong Kong, India, Indonesia, Laos, Macau, Malaysia, Myanmar, Philippines, Singapore, Sri Lanka, Thailand, Vietnam

Product features, specifications and appearances are subject to change without notice. This product is manufactured, distributed, and sold by All ID Asia. ©2022 All Rights Reserved. Polaroid, Polaroid Color Spectrum, and Polaroid Classic Border Logo are trademarks of PLR IP Holdings, LLC used under license. All other trademarks are the property of the respective owner, who has not sponsored, endorsed or approved this product. PLR IP Holdings, LLC does not manufacture this product or provide any Manufacturer's Warranty or support.