



NLS-PP310

PORTABLE LABEL PRINTER

FEATURES

- **Ergonomically designed, one-hand printer**

Lightweight and mini size make it easily carried and operated in one hand, which reduces the user's fatigue meantime

- **High Printing Speed.**

Up to 76mm/s print speed let the shipment receipt print less than 3S and highly enhances the efficiency

- **Strong Durability**

High protection IP 42 and 1.5m drop make it durable in the challenging outside workplace

- **Reliable print head**

NLS-PP310 uses reliable print head technology to improve the print head lifetime and still can provide clear and fast printing.



Reliable Label Production



High-Speed Printing



One-hand Printer



IP sealing



Drop



Bluetooth

NLS-PP310

Performance

Resolution	203dpi x 203dpi
Printing	Direct Thermal
Max. Print Width	72mm
Max. Print Speed	76mm/s (receipt printing); 50mm/s (label printing)
Programming Language	ESC/POS, CPCL
Memory	FLASH:4MB; SDRAM: 8MB
Interface	USB, Bluetooth 4.0
Sensor	Black Mark, Gap, Media Out sensing

Media

Media Type	Direct Thermal media, continuous receipt, black mark receipt, gap label
Media Roll Size	Max. outer diameter: 40mm Max. width: 80mm
Media Thickness	Continuous receipt/black mark receipt: 0.06mm-0.10mm Label: 0.06mm-0.16mm
Media Cutting	Tear off

Characters/Graphics/Symbologies

Symbologies	1D(ESC/POS): UPC-A, UPC-E, JAN13 (EAN13), JAN 8 (EAN8), CODE39, ITF, CODABAR, CODE93, CODE128 2D(ESC/POS): PDF417, QR CODE, MAXICODE, GSI 1D(CPCL): UPC-A, UPC-E, JAN13 (EAN13), JAN8 (EAN8), CODE39, CODE93, Interleaved 2 of 5, Interleaved 2 of 5 with checksum, CODE128, UCC EAN 128, CODABAR, MSI 2D(CPCL): PDF417, QR CODE
Characters	Standard Font A (12x24), Font B (9x17), user-defined characters Kanji (24x24); support Chinese (2312), English (ASCII), support Simplified Chinese (18030 or GBK), traditional Chinese, English, Japanese, Korean (Optional), can download custom characters to FLASH or RAM
Graphics	Binary unformatted bitmap, HEX, BMP and IMG image files can be downloaded to FLASH, RAM

Physical

Dimension	109mm(L)x105mm(W)x51mm(H)
Weight	330g (with battery)
Power Adapter	Input: AC 100~240V, 50/60Hz; Output: DC 12V±0.6V, 1A
Battery	1400mAh Li-polymer Battery
Charging Time	2.5-3 hours
Sealing	IP42 with waist bag
Drop	1.5m
Reliability	Print head lifetime :50Km(Standard test condition)

Newland AIDC

Add: No.1 Rujiang West Rd.,
Mawei, Fuzhou, Fujian 350001, China
Tel: +86-591-83979500
Fax: +86-591-83979216
Email: info@newlandaidc.com
Web: www.newlandaidc.com

Asia Pacific

Add: 6 Raffles Quay #14-06
Singapore 048582
Email: info@newlandaidc.com

Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,
The Netherlands
Tel: +31 (0) 345 87 00 33
Email: sales@newland-id.com
Tech Support: tech-support@newland-id.com

North America & Latin America

Add: 46559 Fremont Blvd.,
Fremont, CA 94538, USA
Tel: +1 510 490 3888
Fax: +1 510 490 3887
Email: info@newlandaidc.com

NLS-PP310

Software

SDK Windows, Linux, Android, Mac

Certificate

Certificate CE, BIS, FCC

Specifications are subject to change without notice.

2022/11/17 Version: V1.2

Newland AIDC

Add: No.1 Rujiang West Rd.,
Mawei, Fuzhou, Fujian 350001, China
Tel: +86-591-83979500
Fax: +86-591-83979216
Email: info@newlandaidc.com
Web: www.newlandaidc.com

Asia Pacific

Add: 6 Raffles Quay #14-06
Singapore 048582
Email: info@newlandaidc.com

Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,
The Netherlands
Tel: +31 (0) 345 87 00 33
Email: sales@newland-id.com
Tech Support: tech-support@newland-id.com

North America & Latin America

Add: 46559 Fremont Blvd.,
Fremont, CA 94538, USA
Tel: +1 510 490 3888
Fax: +1 510 490 3887
Email: info@newlandaidc.com